

VFI-730 Polyurethane Foam

Advanced formula, energy efficient, long lasting, sprayable foam product offered in three reactivity grades.

Environmentally Safe
Dade County Approved
UL Approved

VFI-730 Polyurethane Spray Foam is self-flashing, easily renewable and improves drainage.

Volatile Free's VFI-730 SPF forms a superior roofing system that can extend an existing built-up roof's life up to 15 years.

*Non-prorated, leak-free warranty**



***Save time and money.
No need to remove properly prepared, existing roof substrates.***



An additional benefit!

Your questions will be answered by one of our chemists or technicians. They're just a toll free phone call away.



VOLATILEFREETM INCTM
MANUFACTURERS OF HIGH PERFORMANCE POLYMERS

Toll Free 800.307.9218 Tel 262.787.0400 Fax 262.787.0500

Email info@volatilefree.com Web www.volatilefree.com

VFI-730 foam can cover more square feet of roof than any other brand.

VFI-730 Polyurethane Spray Foam lowers heating and cooling costs.

- **No seams - no leaks.** Volatile Free's VFI-730 SPF in combination with VFI-540 Aluminum Polyurea Hybrid Coating, VFI-550 + Aluminum, Single Component Urethane Coating or VFI-535 Copper Coating forms a superior, seamless roofing system.
- **Self-flashing** - conforms to any shape and leaves no gaps.
- **Renewable** - The roof's future integrity is easily renewable through the application of one of Volatile Free's environmentally safe elastomer coatings.
- **Lightweight** - The stone ballast that is removed weighs more than the foam that replaces it, reducing roof sag risk. Better snow load tolerance.
- **Longer life** - The VFI Roof Coating System will encapsulate and protect the roof and recoating can extend the roof's life up to 15 years.



**VFI Roofing Systems, when professionally installed and properly maintained, are covered by a non-prorated, leak-free warranty.*

Exceptional wind uplift resistance.

"The application of sprayed foam to steel deck and plywood deck demonstrated uplift load resistance up to the capacity of the test equipment to develop load (160-165 psf) without any sign of delamination or other damage to the foam."

-Underwriters Laboratory, Inc.

VFI-730 Polyurethane Foam...see the difference. Try it today.
Volatile Free, Inc. is an Industry Leader in Polyurea Hybrid Elastomer Coatings.

This information and technical advice provided herein are believed to be reliable and accurate to the best knowledge of Volatile Free, Inc., as based on tests and should serve only as a recommendation. As the manufacturer, Volatile Free, Inc. makes no representations or warranties of any kinds, expressed, implied or statutory, including but not limited to all implied warranties of merchantability or fitness for use or a particular purpose for the product. Volatile Free, Inc. makes no representations or warranties as to the results of the use of the product and assumes no obligation or liability in connection therewith. Volatile Free, Inc. is not liable for any incidental or consequential damages of any sort from use of this product. The information provided herein is subject to change at any time without notice. Information changes may include, but are not limited to, commercial and technical changes, changes in pricing, physical characteristics and packaging.