

VFI-540 Aluminum Elastomer Roof Coating

Save time and money.

No need to remove existing substrates.

Non-Prorated Warranty*

Environmentally Safe
Dade County Approved
UL Approved

- Reflects UV rays - maintains lower surface temperatures
- Lowers air-conditioning costs
- Self-flashing
- Excellent weatherability
- Seamless - no leaks
- Can be applied to different substrates
- Easy maintenance



VFI is the Original Manufacturer of Polyurea Hybrid Aluminum Roof Coatings.

An additional benefit!

Your questions will be answered by one of our chemists or technicians. They're just a toll free phone call away.



VOLATILEFREE^{INC}
MANUFACTURERS OF HIGH PERFORMANCE POLYMERS

Toll Free 800.307.9218 Tel 262.787.0400 Fax 262.787.0500
Email info@volatilefree.com Web www.volatilefree.com



The industry leader in polyurea hybrid elastomer roof coatings.

Why settle for less and pay up to 50% more?



Volatile Free's VFI-540 spray polyurea hybrid aluminum elastomer roof coating forms a superior, advanced monolithic roofing system that will encapsulate and protect the roof better than other roofing systems.

Less expensive to apply than other roof coating systems. Only one coat of VFI-540 is required to achieve the same final coating thickness as two or three coats of other products.

****VFI's Roofing Systems, when professionally applied and maintained, are covered by a non-prorated, leak-free warranty.***

Additional advantages in using VFI-540:

- Excellent weatherability - QUV Weatherometer exposure tests, equivalent to 15 years, showed no visible deterioration or change in physical properties.
- Advanced polymer hybrid technology has produced a polymer coating with high tensile strength, elongation, hardness and tear resistance physical properties.
- Self-flashing greatly reduces or eliminates parapet, stack, vent and pitch pocket leaks.
- Seals cracks and crevices better than other roofing products due to its elastomer properties.
- Superior protection from leaks, rust and corrosion on metal roofs.
- Sets up instantly and is tack-free in 10 to 30 seconds. Totally dry in less than 30 minutes.
- Renewable through easy recoating - easy maintenance without compromising the integrity of the roof.
- Available in copper color



High UV resistance provides lower roof temperatures and lower cooling costs.



EPDM = 150°



Hypalon = 126°



VFI-540 = 96°

Specify VFI-540... your value buy!

Contact us today for more information.

This information and technical advice provided herein are believed to be reliable and accurate to the best knowledge of Volatile Free, Inc., as based on tests and should serve only as a recommendation. As the manufacturer, Volatile Free, Inc. makes no representations or warranties of any kinds, expressed, implied or statutory, including but not limited to all implied warranties of merchantability or fitness for use or a particular purpose for the product. Volatile Free, Inc. makes no representations or warranties as to the results of the use of the product and assumes no obligation or liability in connection therewith. Volatile Free, Inc. is not liable for any incidental or consequential damages of any sort from use of this product. The information provided herein is subject to change at any time without notice. Information changes may include, but are not limited to, commercial and technical changes, changes in pricing, physical characteristics and packaging.