

VFI-540 on Single-ply Roofing

**Save time and money.
No need to remove
existing substrates.**

No V.O.C.'s
Environmentally Safe
Dade County Approved
UL Approved

- No leaks - Water will not migrate through
- Self-flashing - Forms to irregular shapes - No caulking
- Seamless - No need for tape
- Long lasting
- Renewable through easy recoating
- Easy maintenance
- Minimizes thermal shock - Lower surface temperature
- No additional non-biodegradable roofing material in your local land fill
- Chemically stable
- Fast and easy application
- **Non-prorated warranty***



An additional benefit!

Your questions will be answered by one of our chemists or technicians. They're just a toll free phone call away.



VOLATILEFREE INCTM
MANUFACTURERS OF HIGH PERFORMANCE POLYMERS

Toll Free 800.307.9218 Tel 262.787.0400 Fax 262.787.0500
Email info@volatilefree.com Web www.volatilefree.com



***Volatile Free, Inc. ...the original manufacturer of
Polyurea Hybrid Aluminum Elastomer Roof Coatings.***

A leak-free roof at half the cost.

Save up to half the labor and material cost by installing a high performance roofing system that eliminates the need to remove and replace the old single-ply roofing material!

Get additional savings on maintenance costs since there is no tape or caulk to dry out over time. VFI-540 is **self-flashing** which greatly reduces or eliminates parapet, stack, vent and pitch pocket leaks.

Shrinking single-ply material and separating seams will be bridged and sealed by the VFI-540 due to its seamless, elastomeric physical properties.

Existing p-gravel, river rock or paver block ballast will be eliminated on a properly secured single-ply roof. This will reduce the weight on the roof by 10 to 20 pounds per square foot. VFI-540 will also tightly coat and seal all single-ply fasteners.

A single-ply roof offers only one layer of protection. Applying VFI-540 Aluminum polyurea hybrid coating over existing single-ply roofing adds a tougher layer of sealant protection against abrasion and weather related deterioration.

****VFI Roofing Systems, when professionally installed and properly maintained, are covered by a non-prorated, leak-free warranty.***



Self-flashing



VFI-540 over single-ply roofing material will reduce your interior climate control cost by reflecting sunlight and lowering the roof's temperature.



EPDM = 150°



Hypalon = 126°



VFI-540 = 96°

Possible tax advantage!

Removal and replacement of an existing single-ply roof is a capital investment. Applying VFI-540 Aluminum polyurea hybrid elastomer coating over an existing single-ply roof is a repair and therefore could be tax deductible. (Consult your tax advisor.)

Specify VFI-540!

Contact us today for more information.

This information and technical advice provided herein are believed to be reliable and accurate to the best knowledge of Volatile Free, Inc., as based on tests and should serve only as a recommendation. As the manufacturer, Volatile Free, Inc. makes no representations or warranties of any kinds, expressed, implied or statutory, including but not limited to all implied warranties of merchantability or fitness for use or a particular purpose for the product. Volatile Free, Inc. makes no representations or warranties as to the results of the use of the product and assumes no obligation or liability in connection therewith. Volatile Free, Inc. is not liable for any incidental or consequential damages of any sort from use of this product. The information provided herein is subject to change at any time without notice. Information changes may include, but are not limited to, commercial and technical changes, changes in pricing, physical characteristics and packaging.